

Q-Gate Pro (NQ-910-EU)



Technical Specifications:

Interface

USB	<ul style="list-style-type: none">• 1 x USB 2.0
Console	<ul style="list-style-type: none">• 1 x UART for Console

Wireless Characteristics

Ethernet	<ul style="list-style-type: none">• Gigabit Ethernet x1 Port (10/100/1000 Mbps)
GPRS	<ul style="list-style-type: none">• Wireless (2G) access to internet• OSGi/JVM support• FOTA support
Wi-Fi	<ul style="list-style-type: none">• Wi-Fi: IEEE 802.11n
Z-Wave	<ul style="list-style-type: none">• Supports EU Z-Wave sub-1 GHz frequency bands

Operating Conditions

Operating Temperature Range	0°C - +40°C
Operating Humidity Range	10% - 90% (non-condensing)

Features

Max. number of supported devices	80
---	----

Z-Wave supported classes

Device class	GENERIC_TYPE_STATIC_CONTROLLER
Specific device class	SPECIFIC_TYPE_PC_CONTROLLER
Command class	COMMAND_CLASS_ZWAVEPLUS_INFO COMMAND_CLASS_VERSION COMMAND_CLASS_MANUFACTURER_SPECIFIC COMMAND_CLASS_ASSOCIATION_GRP_INFO COMMAND_CLASS_ASSOCIATION COMMAND_CLASS_DEVICE_RESET_LOCALLY COMMAND_CLASS_APPLICATION_STATUS COMMAND_CLASS_CRC_16_ENCAP COMMAND_CLASS_POWERLEVEL COMMAND_CLASS_TIME COMMAND_CLASS_MULTI_CMD COMMAND_CLASS_SECURITY COMMAND_CLASS_MARK COMMAND_CLASS_BASIC COMMAND_CLASS_SECURITY COMMAND_CLASS_ASSOCIATION_GRP_INFO COMMAND_CLASS_ASSOCIATION COMMAND_CLASS_MULTI_CHANNEL_ASSOCIATION COMMAND_CLASS_CRC_16_ENCAP COMMAND_CLASS_WAKE_UP COMMAND_CLASS_MULTI_CHANNEL

All specifications are subject to change and improvement without notice!

